

PUMP KIT with REAL CLEAN SYSTEM

for the
REAL UVT ONLINE MONITOR



The Pump Kit option for the Real UVT Online monitor allows for easy installation in open channel or non-pressurized/gravity feed applications.

The Pump Kit is designed for continuous operation and includes the Real Clean automatic chemical cleaning system built in to the Pump Kit's enclosure. More details about the Real Clean system can be found by referring to the Real Clean product specification sheet.

REAL PUMP KIT TECHNICAL SPECIFICATIONS

PUMP	Long life rotating piston pump
FLOW RATE	500 ml/min
PRIMING	Self priming to 15 ft vertical lift
TURBIDITY	Pump design allows pumping of high turbidity water with ease
OPERATION	Pump designed for continuous operation
PRESSURE RELIEF	Automatic safety pressure relief incorporated
FLUID CONNECTIONS	25 ft - 1/2 " OD suction tube included
FILTER	100 micron stainless steel washable filter screen
CONTROLLER	Automatic control of pump timing and valve operation
HEIGHT	18"h x 20"w x 9"d
ENCLOSURE	NEMA 4X, wall mountable
WEIGHT	20 lbs
ELECTRICAL	115 VAC 1.5 amps (includes 24 DC power supply for Real UVT Online monitor and Real Clean System)
STORAGE TEMP	-20 to 60°C (-4 to 140°F)
OPERATING TEMP	0 to 45°C (32 to 113°F)
WARRANTY	2 year limited warranty